



Unit: mm

**1/3"**

Max. Sensor Size

**MANUAL**

Manual Iris

**CS**

CS

1. Aspheric surface technology ensure the high quality image.
2. Big Iris F1.3, suitable for dark invisible light environment.
3. The super multi-layer coating reduces flare and ghosting.
4. Professional precision machining offers high quality lens.

<b>Code</b>	PMS-2713SCSIR	
<b>Focal Length</b>	2.7mm-13mm	
<b>Iris Range</b>	F1.3	
<b>Max. Sensor Size</b>	1/3"	
<b>Field of View (D x H x V)</b>	1/3"	W:123°x98°x77.3° T:28.6°x22°x16.5°
	1/4"	W:92°x73.1°x54.6° T:21.5°x17.1°x15.8°
<b>Focusing Range</b>	0.3mm-∞	
<b>Control</b>	<b>Zoom</b>	Manual
	<b>Focus</b>	Manual
	<b>Iris</b>	DC Automatic
<b>Effective Aperture</b>	<b>Front</b>	25.6mm
	<b>Back</b>	8.6mm
<b>Back Focal Length(in air)</b>	W:8.77mm T:20.7mm	
<b>Mount</b>	CS	
<b>Working Temperature</b>	-10°C ~ +50°C	
<b>Weight</b>	78g	